



# United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/942,759	08/31/2001	Junko Ami	213504US2RD	9942
22850 75	7590 04/20/2006		EXAMINER	
OBLON, SPIVAK, MCCLELLAND, MAIER & NEUSTADT, P.C. 1940 DUKE STREET ALEXANDRIA, VA 22314			WIN, AUNG T	
			ART UNIT	PAPER NUMBER
	,		2617	
			DATE MAILED, 04/20/200	ć

Please find below and/or attached an Office communication concerning this application or proceeding.

	Application No.	Applicant(s)			
	09/942,759	AMI ET AL.			
Office Action Summary	Examiner	Art Unit			
٦٠	Aung T. Win	2645			
The MAILING DATE of this communication app Period for Reply	ears on the cover sheet with the c	orrespondence address			
A SHORTENED STATUTORY PERIOD FOR REPLY THE MAILING DATE OF THIS COMMUNICATION.  - Extensions of time may be available under the provisions of 37 CFR 1.13 after SIX (6) MONTHS from the mailing date of this communication.  - If the period for reply specified above is less than thirty (30) days, a reply If NO period for reply is specified above, the maximum statutory period w  - Failure to reply within the set or extended period for reply will, by statute, Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	6(a). In no event, however, may a reply be tim within the statutory minimum of thirty (30) days ill apply and will expire SIX (6) MONTHS from cause the application to become ABANDONE	ely filed s will be considered timely. the mailing date of this communication. O (35 U.S.C. § 133).			
Status					
1) Responsive to communication(s) filed on 11/29	<u> 1/2005</u> .				
2a) ☐ This action is <b>FINAL</b> . 2b) ☒ This	action is non-final.				
3) Since this application is in condition for allowan closed in accordance with the practice under <i>E</i>					
Disposition of Claims					
4) ☐ Claim(s) 1-12,19 and 21 is/are pending in the a 4a) Of the above claim(s) is/are withdraw 5) ☐ Claim(s) is/are allowed. 6) ☐ Claim(s) 1-12,19 and 21 is/are rejected. 7) ☐ Claim(s) is/are objected to. 8) ☐ Claim(s) are subject to restriction and/or	vn from consideration.	·.			
Application Papers					
9) The specification is objected to by the Examine	r.				
10) The drawing(s) filed on is/are: a) accepted or b) objected to by the Examiner.					
Applicant may not request that any objection to the	<del>*</del> `',	· ·			
Replacement drawing sheet(s) including the correcting 11) The oath or declaration is objected to by the Ex					
Priority under 35 U.S.C. § 119					
12) △ Acknowledgment is made of a claim for foreign  a) △ All b) ☐ Some * c) ☐ None of:  1. △ Certified copies of the priority documents  2. ☐ Certified copies of the priority documents  3. ☐ Copies of the certified copies of the priority application from the International Bureau  * See the attached detailed Office action for a list	s have been received. s have been received in Applicati ity documents have been receive ı (PCT Rule 17.2(a)).	on No ed in this National Stage			
Attachment(s)	_				
Notice of References Cited (PTO-892)     Notice of Draftsperson's Patent Drawing Review (PTO-948)	4) 🔲 Interview Summary Paper No(s)/Mail Da				
Notice of Draftsperson's Patent Drawing Review (P10-948)     Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)     Paper No(s)/Mail Date		atent Application (PTO-152)			

Art Unit: 2645

#### **DETAILED ACTION**

### Claim Rejections - 35 USC § 112

The following is a quotation of the first paragraph of 35 U.S.C. 112:

The specification shall contain a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make and use the same and shall set forth the best mode contemplated by the inventor of carrying out his invention.

Claims 1-12, 19 and 21 are rejected under 35 U.S.C. 112, first paragraph, as failing to comply with the written description requirement. The claim(s) contains subject matter which was not described in the specification in such a way as to reasonably convey to one skilled in the relevant art that the inventor(s), at the time the application was filed, had possession of the claimed invention.

Examiner cannot find any support in the disclosure to Claims' limitation "without connecting said each reception device --- with said one transmission device" as cited in Claim 1, 19 and 21. Examiner requests the applicant specify the drawing, page, column or line number, which support the claim limitation. Applicant is required to cancel the new matter in the reply to this Office Action.

## Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Art Unit: 2645

1. Claims 1-12, 19 & 21 are rejected under 35 U.S.C. 103(a) as being unpatentable over Callaway (U.S. Patent Number: US006275500B1) in view of Haartsen (U.S. Patent Number: US006590928B1).

Regarding Claims 1 and 21, Callaway discloses a broadcast type service system (Bluetooth 1.0 system; Background) comprising:

at least one transmission device (at least one of a plurality of communication devices acting as slaves capable of communication with the master and capable of communication with at least another one of the plurality of communication devices); a reception information providing device (a transceiver operating as master); and a plurality of reception devices (a plurality of communication devices acting as slaves) [Column 5, Line 10-17]

each transmission device (a first slave of the plurality of communication devices)
having: a transmission device communication unit (Transceiver 50) [Figure 15]
configured to carry out communications with the reception information providing device
(Master communication device) and the reception devices (a plurality of communication
devices acting as slaves) (configured to transmit a communication request to the master
communication device to carry out communication with the reception devices) and a
transmission device control unit (Processor 58) [Figure 15] configured to control the
transmission device communication unit to transmit application data (data packets) to at
least one reception device (a second slave of the plurality of communication devices)
and to transmit (transmit to request) a reception establishing information of each

Art Unit: 2645

transmission device (communication resource parameter such as frequency, modulation, protocol, data rate, etc.) [Column 3, Line 50-52 and Line 63-67] which is necessary for a reception device to receive the application data transmitted from each transmission device [Figure 13] [Column 5, Line 9-39] [Column 7, Line 19-46]; the reception information providing device (Master communication device) having: a reception information providing device communication unit (Transceiver acting as master) configured to carry out communications with each transmission device (a first slave of the plurality of communication devices) and the reception devices (the plurality of slaves communication devices); and a reception information providing device control unit (Processor 58) configured to control the reception information providing device communication unit to receive the reception establishing information (communication resource parameter such as frequency, modulation, protocol, data rate, etc.) of each transmission device transmitted from each transmission device (to receive acknowledgement of the reception establishing information from a first slave of the plurality of communication devices), and to transmit the reception establishing information of a specified transmission device to a prescribed reception device (to transmit the reception establishing information assigned to a first slave of the plurality of communication devices to a second slave of the plurality of communication devices) [Column 3, Line 26-30] [Figure 13] [Column 5, Line 9-39] [Column 7, Line 19-46]; and each reception device having (a second slave of the plurality of communication devices): a reception device communication unit (Transceiver) configured to carry out

communications with each transmission device and the reception information providing

Art Unit: 2645

device; and a reception device control unit (processor) configured to control the reception device communication unit to receive the reception establishing information of one transmission device (a first slave of the plurality of communication devices) transmitted from the reception information providing device (master communication device), and to receive the application data (data packet) transmitted from said one transmission device according to the reception establishing information of said one transmission device (according to the reception establishing information assigned to a first slave of the plurality of communication devices) [Figure 13] [Column 5, Line 9-39] [Column 7, Line 19-46].

Callaway discloses that the reception information providing device (Master communication device) directs and sets up the second communication source in order for the transmission device and reception device to communicate each other directly for higher data link. Callaway also teaches that the master act as the intermediary for all slave-to-slave communications under Bluetooth 1.0 system for parked slaves but Callaway fails to explicitly disclose that all the parked slaves device communicate each other indirectly through the master device.

Haartsen also discloses a star topology configuration of the wireless network including master and slave units. Haartsen also teaches that slaves cannot communicate directly with each other, but need to use the master as an intermediary device [Column 12, Line 32-34].

Application/Control Number: 09/942,759 Page 6

Art Unit: 2645

Therefore, it would have been obvious to one of ordinary skill in the art to modify Callaway broadcast type system with the star topology as taught by Haartsen in order for the transmission device to transmit application data to the reception device without connecting the reception device directly with the transmission device by using the master device (a reception information providing device) as intermediary device. One of ordinary skill in the art would have been motivated to do this to provide variable data rate services to the subscribers depending on the subscribers' demands.

- 2. Regarding Claim 19, which is a method claim corresponding to Claim 1 is rejected for the same reasons as stated above because the claimed steps read on the corresponding means on Claim 1.
- 3. Regarding Claims 2 and 3, Callaway discloses all the limitation in the Claim 1. Callaway further discloses the programmable processor integrated in Bluetooth Tranceiver 50 [Figure 15]. Therefore one of ordinary skilled in the art would have recognized that the reception information providing device is implemented with either a memory unit to store the reception establishing information received by the reception device communication unit for the processor to process in accordance with the reception establishing information or implemented with a plurality of memory units configured to separately store the reception establishing information of a plurality of transmission devices (transmission devices from different piconets) by the reception device communication unit.

Art Unit: 2645

4. Regarding Claim 4, Callaway discloses all the limitations in Claim 1 and further discloses the acknowledgement step initiated by master communication device necessary for the two communication devices agreement to the parameters assigned by the master communication devices [Column 3, Line 56-67]. Therefore, one of ordinary skilled in the art would have recognized that the master communication device (the reception information providing device) is capable of performing service specification comparison between two communication devices and controlling the communications at an acceptable communication level between two communication devices.

Page 7

- 5. Regarding Claim 5, Callaway further discloses that the transmission device control unit of each transmission device is also configured to control the transmission device communication unit to transmit the application data (data packets) even when there is no reception device (second slave of plurality of communication devices) that is carrying out communications with each transmission device (a first slave of plurality of communication devices) in an active mode according to the Bluetooth specification (a first slave of plurality of communication devices communicates a second slave of plurality of communication devices in parked mode) [Column 3, Line 30-32].
- 6. Regarding Claim 6, Callaway further discloses that the reception device control unit is also configured to control the reception device communication unit to receive the application data (data packets) transmitted from said one transmission device (a first

Application/Control Number: 09/942,759 Page 8

Art Unit: 2645

slave of plurality of communication devices) according to the reception establishing information of said one transmission device (according to the assigned resource parameters of a first slave of plurality of communication devices such as frequency, modulation, protocol, data rate, etc), only when communications in an active mode according to the Bluetooth specification cannot be carried out with said one transmission device (transmission device carry out transmission only in parked mode) [Column 3, Line 30-32].

7. Regarding Claims 7 & 8, Callaway discloses that the reception establishing information that indicates (communication resource parameter such as frequency, modulation, protocol, data rate, etc.) as describes in Claim 1. Although Callaway teaches that all devices in the same Piconet are synchronized to the same hopping sequence (hopping pattern) and each piconet is identified by a different frequency hopping sequence [Column 1, Line 55-60], Callaway does not clearly disclose the reception establishing information indicates the phase and clock of transmission device and Bluetooth device.

Haartsen clearly discloses the ad-hoc wireless network in which master and slave units establish communication by the address (Bluetooth address) of master unit, which determines the hopping sequence and the system clock in the master transceiver unit which determines the phase in the hopping sequence [Column 11, Line 31-47]. Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention was made that reception establishing information received by the reception

Art Unit: 2645

device indicates a hopping pattern, Bluetooth device address, a phase and clock of transmission device as taught by Haarten to establish communication between transmission and reception device.

8. Regarding Claim 9, Callaway discloses that the reception establishing information that indicates (communication resource parameter such as frequency, modulation, protocol, data rate, etc.) as describes in Claim 1. Although Callaway teaches that all devices in the same Piconet are synchronized to the same hopping sequence (hopping pattern) and each piconet is identified by a different frequency hopping sequence [Column 1, Line 55-60]. Callaway does not clearly disclose the reception information providing device communication unit transmits the reception establishing information of the specified transmission device that indicates a Bluetooth device address of the specified transmission device, a clock offset between the specified transmission device and the reception information providing device, and a clock of the reception information providing device at a time of transmitting the reception establishing information to the prescribed reception device.

Haartsen discloses master communication means and slave communication means [Figure 12] [Column 20, Line 63-67] [Column 21, Line 1-18] to generate the hop frequencies at appreciate times (synchronized to the same hopping sequence) based on the master address and determination of the clock difference (clock offset) between the master clock and slave clock after connection has been established (link establish

Art Unit: 2645

procedure known to one skilled in the in ad-hoc wireless network art in which master determine the slave Bluetooth device address). Haartsen further discloses bridge unit C participating in different piconets 603 and 605 acting as a bridge between the source unit A in the piconet 603 and destination unit B in piconet 605 [Figure 6b] [Column 14. Line 21-53]. Haartesen clearly teaches that bridge unit comprises two transceiver units. each establish connection with unit A and unit B separately and information is transferred back and forth between two transceiver with bridge unit C by inquiry process which determine the unit addresses of both piconet 603 and piconet 605, and control information. Therefore it would have been obvious to one of ordinary skill in the art at the time of the invention was made to modify reception providing device in Callaway as taught by Haartsen so that the reception information providing device communication unit transmits the reception establishing information of the specified transmission device that indicates a Bluetooth device address of the specified transmission device, a clock offset (time difference) between the specified transmission device and the reception information providing device, and a clock of the reception information providing device at a time of transmitting the reception establishing information to the prescribed reception device to establish connection between the transmission and reception device in different piconets.

Page 10

9. Claim 10 is rejected for the same reason described above in Claim 9 since clock offset is the function of a clock of the specified transmission device at a time of transmitting the reception establishing information from the specified transmission

Art Unit: 2645

device to the reception information providing device and a clock of the reception information providing device at a time of receiving the reception establishing information from the specified transmission device.

- 10. Regarding Claim 11, Callaway discloses that the reception information providing device communication unit (master communication device) receives the request of the reception establishing information of each transmission device by carrying out communications according to the Bluetooth specification (Standard Bluetooth 1.0) with each transmission device [Column 3, Line 42-45].
- 11. Regarding Claim 12, Callaway discloses all the limitations in the Claim 1 but does not disclose the reception information providing device communication unit carry out communication with each transmission device by communications different from the Bluetooth specification.

Haartsen discloses the ad-hoc wireless network in which master and slave units establish communication by means of a virtual frequency hopping channel whose hopping sequence is a function of the master address, and whose phase is a function of the master clock [Abstract]. Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention was made to modify Callaway as taught by Haartsen to carry out data communication different from communications according to the Bluetooth specification with each transmission device to operate in different existing data network to provide mechanisms for efficient distribution of data packets.

Art Unit: 2645

#### Conclusion

Page 12

The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

Haartsen et al. Patent No.: U.S. 6,570,857 B1

Haartsen Patent No.: U.S. 6,754,250 B2

Haartsen Patent No.: U.S. 6,519,460 B1

Van Valkenburg et al. Patent No.: U.S. 6,775,258 B1

Larsson et al. Patent No.: U.S. 6,751,200 B1

Larrsson et al. Patent No.: U.S. 6,535,498 B1

Ohlenbusch et al. Pub. No.: U.S. 2002/0091785 A1

Fritz et al. Pub. No.: U.S. 2002/0051184 A1

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Aung T. Win whose telephone number is (571) 272-7549. The examiner can normally be reached on 8:30 AM - 5:00 PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Fan Tsang can be reached on (571) 272-7547.

Art Unit: 2645

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Aung T. Win Group Art Unit 2645 March 3, 2006

ELISEO RAMOS-FELICIANO PRIMARY EXAMINER